



- Horizontal, vertical or diagonal installation.
- Torrefied yellow poplar.
- Few, sound knots.
- 1" X 6" (25 mm X 152 mm) nominal. Thickness: $\frac{3}{4}$ " – 19 mm. Covering width: 4 $\frac{7}{8}$ " (124 mm).
- 6 to 16 ft. assorted lengths
- Tongue-and-groove edged profile, with one side (bottom) at 90 degrees and the other (top) at 75 degrees, and planed surface.
- Dressed back with longitudinal grooves to prevent warping and improve ventilation between nailing furring strips.
- Guide lines on male groove; the bottom line is used as a guide for recommended spacing while the top line serves as a guide for nailing.

OPTION: OTHER SPECIES

Other wood species and grades are available on special order.

OPTION: PROTECTION AGAINST UV-RAYS

Siding can be sold with three (3) 100% acrylic Woodplus Ultra 10 pre-coats. The coating offered is semi-translucent and within our range of colors. Factory pre-coating must be carried out in accordance with manufacturer's standards. Coating technical specifications are available upon request.

OPTION: FIREPROOFING

Siding must also be fireproofed with 1 coat of fire retardant product. This treatment must be made in accordance with manufacturer's standards. Fireproofing product specifications are available upon request.

INSTALLATION

The fastening of siding boards must be done in accordance with the instructions explained in our installation manual. This manual is available upon request.

WARRANTY

25 years against rot.

3 years against Woodplus coating cracking or flaking.

See details at Planchersbellefeuille.com