



- Horizontal, vertical or diagonal installation
- Torrefied yellow poplar
- Few, sound knots
- 1" X 6" (25 mm X 152 mm) nominal. Thickness: 3/4" – 19 mm. Covering width: 4 7/8" (124 mm)
- 6 to 16 ft. assorted lengths
- Midway through board height tongue and groove profile, at a 45-degree angle on both edges of planed wood surface
- Dressed back with longitudinal grooves to prevent warping and improve ventilation between nailing furring strips.

#### OPTION: OTHER SPECIES

Other wood species and grades are available by special order.

#### OPTION: PROTECTION AGAINST UV-RAYS

Sidings can be sold with three (3) 100% acrylic Woodplus Ultra 10 pre-coats. The coating offered is semi-translucent and within our range of colors. Factory pre-coating must be carried out in accordance with manufacturer's standards. Coating technical specifications are available upon request.

#### OPTION: FIREPROOFING

Siding must also be fireproofed with 1 coat of fire retardant product. This treatment must be made in accordance with manufacturer's standards. Fireproofing product specifications are available upon request.

#### INSTALLATION

The fastening of the siding boards must be done in accordance with the instructions explained in our installation manual. This manual is available upon request.

#### WARRANTY

25 years against rot.

3 years against Woodplus coating cracking or flaking.

See details at [Planchersbellefeuille.com](http://Planchersbellefeuille.com)